

Package fine vacuum control VACUU·SELECT + VACUU·VIEW extended, KF DN 16

[Link to the website](#)



Product description

The VACUU·SELECT fine vacuum control packages provide an easy-to-use vacuum control option for work down to 10^{-3} mbar. These packages include the VACUU·SELECT controller with fine vacuum gauge, a chemical-resistant inline isolation valve (W-B 15C), and the accessories required for connection to your vacuum system via small flange (KF) connections. VACUUBRAND offers fine vacuum control packages with two different small flange connections. The KF DN 16 fine vacuum control package is compatible with our rotary vane pump models RE / RZ 2.5 to RE / RZ 6 and our HYBRID pump RC 6. The KF DN 25 fine vacuum control package is configured for use with our RE / RZ 9 rotary vane pumps and VACUU·PURE screw pumps. With its intuitive, application-based user interface, the controller allows you to quickly get your fine vacuum process under control. For advanced processes, pre-defined applications can be modified, and new applications can be created to optimize your process conditions. The included inline solenoid valve and sensor are automatically configured via the proprietary VACUU·BUS system.

Performance features

- complete package for vacuum control of all fine vacuum applications in chemical labs, with continuous control range from atmosphere to fine vacuum (10^{-3} mbar)
- graphic user interface for simple operation
- predefined applications for quick, reproducible results
- application editor allows easy customization
- rugged VACUU·VIEW extended gauge with wide measuring range offers superior chemical resistance and mechanical robustness

Ordering data

| Product name | Nominal mains voltage mains frequency | Plug type | Articleno. |
|--|---|---------------------|------------|
| VACUU·SELECT + VACUU·VIEW extended, KF DN 16 | 100-230 V 50-60 Hz | CEE/CH/UK/US/AUS/CN | 20700100 |

Items supplied

Package for fine vacuum control, consisting of: Vacuum controller VACUU·SELECT (without internal vacuum sensor and venting valve) with VACUU·VIEW extended and power supply, solenoid valve W-B 15C KF DN 16, T-piece KF DN 16, hose nozzle DN 10 mm (PP), clamping and sealing rings, ready for use, with manual.

Accessories

- Function extension for VACUU·SELECT controller VACUU·SELECT User Management (20700900)
- Rubber vacuum tubing DN 8 mm (20686001)
- Air admittance valve VB M-B (20674217)
- Function extension for VACUU·SELECT controller VACUU·SELECT User Management (20700900)
- Rubber vacuum tubing DN 8 mm (20686001)
- Rubber vacuum tubing DN 8 mm (20686001)

Technical data

| | |
|--|--|
| Measuring range (mbar) | 1100 - 1×10^{-3} mbar |
| Measuring range (torr) | 825 - 1×10^{-3} torr |
| Control range (mbar) | 1000 - 1×10^{-3} mbar |
| Control range (torr) | 750 - 1×10^{-3} torr |
| Measurement principle | Ceramic diaphragm sensor + ceramic jacketed Pirani sensor |
| Accuracy of measurement | +/- 15% of indicated value in the range 0.01-5 mbar / +/-3 mbar for > 5 mbar |
| Vacuum sensor | VACUU-VIEW extended |
| Temperature coefficient | +/- 0.2 mbar/hPa/0.15 torr /K |
| Vacuum sensor connection | Small flange KF DN 16 / hose nozzle DN 10 mm |
| Venting valve, connection | No |
| Permissible ambient temperature range (operation) | 10 - 40 °C |
| Permissible ambient temperature range (storage) | -10 - 60 °C |
| Max. media temperature (continuous operation) | 40 °C |
| Max. media temperature for short times | 80 °C |
| Material of outer housing | Robust plastic housing with good chemical resistance |
| Protection class IEC 60529 | IP 40 |
| Protection class UL50E | Type 1 |
| Protection class of front side according to IEC 60529 | IP 41 |
| Protection class of front side according to UL50E | Type 2 |
| Dimensions (L x W x H) | 152 x 127 x 41 mm |
| Weight | 0.6 kg |
| Max. breaking capacity / breaking current 24V/VACUU-BUS® | 4 A |
| Cable length connection | 2 m |
| NRTL certification | Yes |

Interface

Ethernet (RJ45): Modbus TCP / USB (Type A): Data transfer, software update, RS-232 (additional adapter required)

Dimension sheet



VACUUBRAND GMBH + CO KG
P.O. Box 1664
97877 Wertheim
T +49 9342 808 5550
F +49 9342 808 5555

info@vacuubrand.com
www.vacuubrand.com

VACUUBRAND®

VACUUBRAND is part of the Brand group, a manufacturer of high-quality and innovative laboratory equipment and vacuum technology with a global team of approx. 1,000 employees.

With highly motivated and qualified employees, we manufacture the world's most comprehensive product family for vacuum generation, measurement and control for the rough and fine vacuum range in the laboratory.

All with one goal:

Enabling our customers to run reliable, safe and efficient processes. This is why we commit ourselves to continuous innovation, first-class performance, and outstanding quality.

Engineering excellence is central to our ability to deliver products and solutions renowned for their quality, durability, and reliability. Innovative technology, high quality materials and extensive testing deliver unmatched performance - engineered and manufactured in Germany.

Together with you, our experts will find the best solution for your application and provide you with first-class service along the way.

BRAND (Shanghai) Trading Co., Ltd.
Shanghai, China

T +86 21 6422 2318
info@brand.com.cn
china.brand.com.cn

BRAND Scientific Equipment Pvt. Ltd.
Mumbai, India

T +91 22 42957790
customersupport@brand.co.in
www.brand.co.in

BRANDTECH® Scientific, Inc.
Essex, CT. United States of America

T +1 860 767 2562
info@brandtech.com
www.brandtech.com