

Vacuum pump (oil-free)



Rocker 300



Rocker 300 DC

Rocker 300 / 300 DC up to -680 mmHg, 25 l/min, 50dB

Ideal for:

- filtration for microbiology test
- air sampling
- suspended solid test
- vacuum filtration

Features:

- lubricant and oil free piston
- no air pollution
- maintenance-free
- Prote™ filter prevents liquid from being sucked into the pump and filters particles as well as moisture
- CE certified

Safety mechanism:

- thermal protection device ensures shutting down the pump when overheated and resumes working when the temperature cooled down

 **FAVS**
Scientific Equipment

Tel. 051501153

www.favs.it • info@favs.it

Model	Rocker 300		Rocker 300 DC
Max. power (W)	65	60	35
Max. current (A)	0.7	0.3	3
Max. vacuum	-680 mmHg		-650 mmHg
Max. flow rate	23 l/min	20 l/min	25 l/min
Moisture trap / vacuum regulator	Yes		Yes
Overflow protection	Yes		Yes
Motor ration	1750 rpm	1450 rpm	1800 rpm
Horse power	1/8 HP		1/8 HP
Noise level	50 dB		50 dB
Port thread	5/16 inch (8 mm)		5/16 inch (8 mm)
Net weight	4.1 kg		3.5 kg
Dimension (LxWxH)	26.8 x 13.5 x 20.4 cm		26.8 x 13.5x 20.4 cm
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz		
Order number 110V	00829 167300-11	-	-
Order number 230V	-	00829 167300-22	-
Order number DC 12V	-	-	00829 167330-00