



Bath | circulation water bath

circulation water bath, 6 / 11 / 22 / 30 l, up to 250°C ±0.1°C, 16 l/min, flat lid included



WCH 250°C, 16 l/min, 6/12/22/30 l

Ideal for:

- applications at high temperature
- biotechnology, clinical, environmental, medical, petroleum & food industry, pharmaceutical and industrial applications
- connection with evaporators and viscometers is applicable

Features:



- corrosion resistant stainless steel bath with 1.2 mm thickness
- ceramic fiber insulator of 50 mm thickness and powder-coated steel body
- user's self-compensation function to control difference between real temperature and indicated temperature (±10.0°C)
- digital timer function (99hr 59min): delay time and operation time can be controlled
- drain valve mounted and stainless steel flat lid included
- storage function for the set values of temperature and timer
- backlight LCD display
- CE certified and unique serial number for tracing

Safety mechanism:


- overheat and over-current protection
- sensor error detection
- locking mode

Controller:

- digital fuzzy controller with **Jog-Shuttle-switch** (turn + push)



Stainless steel flat lid (included)



Connection for external circulation Ø12.5mm

Model	WCH-8	WCH-12	WCH-22	WCH-30
Capacity	8 l	12 l	22 l	30 l
Temperature range & accuracy	room temperature +5°C - 250°C, ±0.1°C			
Temperature resolution	0.1°C-display, 0.5°C-control			
Temperature uniformity & probe	±0.2°C, PT100			
Heating Power	1.0 kW	1.5 kW	2.2 kW	2.5 kW
External circulation nozzle	inner Ø10.5 mm, outer Ø12.5 mm			
Pump	max. flow rate: 16l/min, max. pressure: 5 psi, max. lift: 2.8m			
Timer & alarm	99hr 59 min (delay & continuous run), error status & timer end			
Effective space	180 x 130 x 155 mm	250 x 130 x 155 mm	340 x 250 x 155 mm	340 x 250 x 200 mm
Internal dimensions (W x D x H)	180 x 320 x 155 mm	250 x 320 x 155 mm	340 x 440 x 155 mm	340 x 440 x 200 mm
External dimensions (W x D x H)	303 x 443 x 569 mm	373 x 443 x 569 mm	463 x 563 x 569 mm	436 x 563 x 614 mm
Packing size & gross weight	470 x 400 x 500 mm, 19 kg	470 x 400 x 500 mm, 21 kg	600 x 490 x 500 mm, 23 kg	600 x 490 x 500 mm, 37 kg
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz			
Order number 230V	DH.WCH00408	DH.WCH00412	DH.WCH00422	DH.WCH00430
Order number 120V	DH.WCH00508	DH.WCH00512	DH.WCH00522	DH.WCH00530